

CLOSED CIRCUIT BLASTERS

PanBlast™ Closed Circuit Blasters are portable dust free blasting units operated by compressed air; and are available in compact light-duty suction blast and heavy-duty pressure blast variants. Both systems are suited for touch up blasting, weld seam blasting, roll repair / etching and plant maintenance.



- Lightweight, compact and portable
- Continuous cycle blast & vacuum in single process
- Compressed air driven venturi vacuum
- Suitable for most abrasive media types



AER85 Light Duty Closed Circuit Blaster
CAT-0801-01-00
Page 414 to 417



LIGHT DUTY



- Ergonomic "Hands-Free" lightweight handle operation
- Multi-pass ultra high efficiency cyclonic separator
- Fully adjustable abrasive reclaimer for all media types
- Pressure-hold Corsa II abrasive metering valve
- Cartridge dust collector with reverse pulse jet cleaning
- Long life boron carbide venturi blast nozzle



AER215 Heavy Duty Closed Circuit Blaster
CAT-0802-01-00
Page 418 to 421



HEAVY DUTY

ABRASIVE RECYCLING SYSTEMS

PanBlast™ Abrasive Recycling Systems are designed for use with single or dual pressure blast pots. Cleaning of abrasives ensures maximum blasting productivity with less airborne dust released, and less wear and tear on associated components while achieving consistency in surface standard cleanliness and profiles.



- Lightweight, compact and portable
- Compressed air driven via twin venturi ejectors
- 10m (33 ft) vacuum hose with abrasive pick up wand
- Vacuum recovery capacity of 1,000 kg (2,200 lbs) per hour



Pow Air Vac Assembly
CAT-0901-01-00
Page 424 to 427

LOW VOLUME



- Fully adjustable abrasive air wash system for all media types
- Media recycling rate of 3,000 kg (6,600 lbs) per hour
- Single cartridge reverse pulse jet dust collector
- Single-phase electrical power
- Suited for use with a single 200 litres (6 ft³) blast pot
- Optional height extensions and storage hoppers
- Adaptable for use as a blast room sweep in recovery system



ProFlo Abrasive Recycling System
CAT-0902-01-00
Page 428 to 431



Extended ProFlo Recycling System
CAT-0902-02-00
Page 432 to 435

MEDIUM VOLUME



- Fully adjustable abrasive air wash system for all media types
- Media recycling rate of 7,000 kg (15,400 lbs) per hour
- Twin cartridge reverse pulse jet dust collector
- Three-phase electrical power
- Suited for use with dual 200 litres (6 ft³) blast pots
- Optional height extensions and storage hoppers
- Adaptable for use as a blast room sweep in recovery system



UltraFlo Abrasive Recycling System
CAT-0903-01-00
Page 436 to 439



UltraFlo Extended Recycling System
CAT-0903-02-00
Page 440 to 443

HIGH VOLUME