

10

RESPIRATOR AIRLINE FILTERS

The PanBlast™ range of respirator airline filters may be used in conjunction with either generic or PanBlast™ respirator blast helmets. Each respirator airline filter removes moisture and odors from the supplied breathing air to enhance operator comfort during use.



CAT-1702-01-00 Page 578 to 581



PBF II-3 WITH MICROMIST



- Incorporates pressure regulator and gauge, pressure relief and drain valves
- Available in single and multi-operator configurations
- CE marked under PED 97/23/EC
- Optional micro mist filter further removes oil mist and sub-micron particulates from the breathing air for AS/NZS1715 compliance

PBF II FILTERS



CAT-1701-01-00 Page 574 to 577



PBF II JUNIOR FILTER

- Incorporates pressure regulator and gauge, safety relief and drain valves
- Freestanding rugged design with carry handle
- CE marked under PED 97/23/EC



CAT-1704-01-00 Page 590 to 591

- Removes moisture & odour from breathing air
- Economical with 3-stage filtration
- Fits industry standard "insertion cartridge" respirator airline filters
- Also fits "flanged cartridge" respirator airline filters via flange adapter kit



AIRLINE FILTER CARTRIDGE



CAT-1605-01-00 Page 570 to 571

- Detects carbon monoxide (CO) in breathing air
- Integral visual and audible alarm with flow and status indicators
- Multi-voltage operation (240/120 VAC and 12 VDC)
- Portable & rugged case
- Optional remote alarm system, with strobe, siren and 20 m (66 ft) cable



AIRLINE CO MONITOR



CAT-1703-01-00 Page 582 to 585



VISIFLO-S

- Incorporates pressure regulator and gauge, safety relief and drain valves
- Available in single and multi-operator configurations
- CE marked under PED 97/23/EC Category I, PS*DN<3000 with 150 psi (1035 kPa) working pressure
- Can be used in horizontally, vertically, wall mounted or free standing
- Optional CO monitoring system mounted directly on filter body

VISIFLO-S WITH CO MONITOR

VISIFLO-S FILTERS



CAT-1703-02-00 Page 586 to 589



VISIFLO-P

- Clear, virtually indestructible housing tube for visual inspection of filter interior
- Incorporates pressure regulator and gauge, safety relief and drain valves
- Available in single and multi-operator configurations
- CE marked under PED 97/23/EC Category I, PS*DN<3000 150 psi (1035 kPa) working pressure
- Can be used in horizontally, vertically, wall mounted or free standing
- Optional CO monitoring system mounted directly on filter body



VISIFLO-P FILTERS

VISIFLO-P FILTERS